

# SAFETY DATA SHEET

## HYCOTE CARB CLEAN

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

**PRODUCT NAME:** HYCOTE CARB CLEAN

**PART No.:** XUK303

**SUPPLIER:** James Briggs Limited  
Salmon Fields  
Royton  
Oldham. OL2 6HZ.

**TEL:** 0161 627 0101

**FAX:** 0161 627 0971

**EMERGENCY TELEPHONE(S):** 0161 620 5400 NOTE! TO BE USED FOR CHEMICAL EMERGENCIES ONLY!!!

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	CONTENTS	HEALTH (class)	RISK (R No.)
XYLENE	1330-20-7	1-5 %	Xn	20/21, 38
n-HEXANE	110-54-3	0-1 %	Xn, N	38, 48/20, 62, 65, 67, 51/53
n-HEPTANE	142-82-5	5-10 %	Xn, N	38, 65, 67, 50/53
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN	64742-49-0	1-5 %	Xn	65
ACETONE	67-64-1	30-60 %	Xi	36, 66, 67
ISOBUTANE	75-28-5	1-5 %		
BUTANE	106-97-8	5-10 %		
PROPANE	74-98-6	10-30 %		

### 3 HAZARDS IDENTIFICATION

Extremely flammable.  
Irritating to eyes.  
Repeated exposure may cause skin dryness or cracking.  
Vapours may cause drowsiness and dizziness.

### 4 FIRST AID MEASURES

**INHALATION:** Move the exposed person to fresh air at once. Get medical attention if any discomfort continues. For breathing difficulties oxygen may be necessary.

**INGESTION:** Ingestion is an unlikely event, but should this occur seek medical advice.

**SKIN:** Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

**EYES:** Spray in the eyes: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING PROCEDURES:** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

# HYCOTE CARB CLEAN

## UNUSUAL FIRE & EXPLOSION HAZARDS:

Aerosol cans may explode in fires. Risk of explosion if heated.

## 6 ACCIDENTAL RELEASE MEASURES

### SPILL CLEANUP METHODS:

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Wear necessary protective equipment. If leakage cannot be stopped, evacuate area. Ventilate well. Larger spill: Do not contaminate water sources or sewer.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS:

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Provide good ventilation.

### STORAGE PRECAUTIONS:

Aerosol cans: Must not be exposed for direct sunlight or temperatures above 50°C.

## 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME	CAS No	STD	LT EXP (8 hrs)	ST EXP (15 min)
XYLENE	1330-20-7	OES.	100 ppm(Sk)	150 ppm(Sk)
n-HEXANE	110-54-3	OES.	20 ppm	No std.
n-HEPTANE	142-82-5	OES.	400 ppm	500 ppm
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN	64742-49-0	SUP.	1000 mg/m3	
ACETONE	67-64-1	OES.	750 ppm	1500 ppm
BUTANE	106-97-8	OES.	600 ppm	750 ppm
PROPANE	74-98-6		Asphyxiating	Asphyxiating

### INGREDIENT COMMENTS:

OES = Occupational Exposure Standard. SUP = Supplier's recommendation.  
Sk = Can be absorbed through skin.

### PROTECTIVE EQUIPMENT:



### VENTILATION:

Provide adequate general and local exhaust ventilation.

### RESPIRATORS:

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).

### PROTECTIVE GLOVES:

Use protective gloves.

### EYE PROTECTION:

Use approved safety goggles or face shield.

### OTHER PROTECTION:

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### HYGIENIC WORK ROUTINES:

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol.	COLOUR:	Varying.
ODOUR/TASTE:	Organic solvents.		
SOLUBILITY DESCRIPTION:	Insoluble in water.	FLAMMABILITY LIMIT (lower %):	0.8
FLAMMABILITY LIMIT (upper %):	13.0		

## 10 STABILITY AND REACTIVITY

### STABILITY:

Normally stable.

### CONDITIONS TO AVOID:

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

# HYCOTE CARB CLEAN

## 11 TOXICOLOGICAL INFORMATION

<b>HEALTH HAZARDS, GENERAL:</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>INHALATION:</b>	Gas or vapour in high concentrations may irritate respiratory system. Gas or vapour displaces oxygen available for breathing (asphyxiant).
<b>SKIN:</b>	Product has a defatting effect on skin. Prolonged or repeated exposure may cause severe irritation.
<b>EYES:</b>	Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting. May cause severe irritation to eyes.
<b>ROUTE OF ENTRY:</b>	Inhalation. Skin and/or eye contact.

## 12 ECOLOGICAL INFORMATION

**ENVIRONMENTAL HAZARDS:** No data is available on the product itself.

## 13 DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS:** Empty containers must not be burned because of explosion hazard. Dispose of in accordance with Local Authority requirements. Contact specialist disposal companies.

## 14 TRANSPORT INFORMATION

**LABEL FOR CONVEYANCE:**



<b>ROAD:</b>			
<b>UN No:</b>	1950	<b>ADR CLASS No:</b>	2
<b>ADR ITEM No:</b>	5F	<b>MARGINAL:</b>	2201
<b>PROPER SHIPPING NAME I:</b>	AEROSOLS		
<b>ROAD TRANSPORT NOTES:</b>	Exempted from control as Limited Quantity provisions apply.		
<b>RAIL:</b>			
<b>RAIL TRANSPORT CLASS No:</b>	2.1	<b>RAILROAD PT:</b>	5F
<b>SEA:</b>			
<b>UN SEA:</b>	1950	<b>SEA TRANSPORT CLASS No:</b>	2.1
<b>IMDG Page No:</b>	2102	<b>SEA PACK GR:</b>	N/A
<b>EmS No.:</b>	2-13	<b>MFAG Table No:</b>	620
<b>MARINE POLLUTANT:</b>	No.		
<b>AIR:</b>			
<b>UN AIR:</b>	1950	<b>AIR TRANSPORT CLASS No:</b>	2.1

## 15 REGULATORY INFORMATION

**LABEL FOR SUPPLY:**



EXTREMELY FLAMMABLE



IRRITANT

<b>RISK PHRASES:</b>	R-12	Extremely flammable.
	R-36	Irritating to eyes.
	R-66	Repeated exposure may cause skin dryness or cracking.
	R-67	Vapours may cause drowsiness and dizziness.

# HYCOTE CARB CLEAN

<b>SAFETY PHRASES:</b>	S-2	Keep out of reach of children.
	S-16	Keep away from sources of ignition - No Smoking.
	S-26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S-37	Wear suitable gloves.
	S-51	Use only in well ventilated areas.
	S-23A	Do not breathe vapour/spray.

**UK REGULATORY REFERENCES:** The Control of Substances Hazardous to Health Regulations 1988.

Chemicals (Hazard Information & Packaging) Regulations 1993.

**UK ENVIRONMENTAL LISTINGS:** Rivers (Prevention of Pollution) Act 1961.

Control of Pollution (Special Waste Regulations) Act 1980.

**STATUTORY INSTRUMENTS:** Chemicals (Hazard Information and Packaging) Regulations.

**APPROVED CODE OF PRACTICE:** Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES:** Occupational Exposure Limits EH40.  
Introduction to Local Exhaust Ventilation HS(G)37.  
CHIP for everyone HSG(108).

## 16 OTHER INFORMATION

**INFORMATION SOURCES:** Dangerous Properties of Industrial Materials Report, N.Sax et.al.

**REVISION DATE:** 11-00

**SAFETY DATA SHEET STATUS:** Approved.

### DISCLAIMER

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS, TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.