

1. Identification of the substance/preparation and company

Trade name

Sonax Paint Renovator
article number 302200-545

Usage

Car Care

Company

Sonax GmbH
Münchener Straße 75

D-86633 Neuburg/Donau

Tel. (0049) 8431/53-0 Fax. (0049) 8431/53390
E-Mail: ERP@sonax.de

Information provided by: Phone (00 49)84 31/53-2 17

Emergency telephone number: 0049 84 31 53-0 (Only during
business hours)

2. Hazards identification

No particular hazards known.

3. Composition/information on ingredients

Chemical characterization

Specification
Emulsion of wax, abrasive, solvent, silicone and water.

Hazardous ingredients

CAS no.	EINECS no.	concentration	haz.sym.	R phrases
---------	------------	---------------	----------	-----------

Hazardous substance name

90622-57-4	292-459-0	5-10 % Xn		R65, R66, R53
------------	-----------	-----------	--	---------------

hydrocarbons isoparaffinic

4. First aid measures

First aid measures / general information
Remove contaminated clothing.

First aid measures / inhalation
Ensure supply of fresh air.

First aid measures / skin contact
In case of contact with skin wash off with water.

First aid measures / eye contact
In case of contact with eyes rinse thoroughly with water

First aid measures / ingestion

Do not induce vomiting.
Refer for medical treatment.

5. Fire-fighting measures**Suitable extinguishing media**

foam
carbon dioxide
dry powder
water spray jet

Extinguishing media that must not be used for safety reasons

6. Accidental release measures**environmental precautions**

Do not discharge into surface waters/groundwater.
Do not discharge into the subsoil/soil.

methods for cleaning up/taking up

Take up with absorbent material (e.g. general-purpose binder).

7. Handling and storage**Handling**

Advice on safe handling
No special measures necessary if used correctly.

Advice on protection against fire and explosion

Storage

Requirements for storage rooms and vessels
Provide solvent-resistant and impermeable floor.

Advice on storage compatibility
Do not store together with food.

Further information on storage conditions

Keep container tightly closed
Keep container in a well-ventilated place
Recommended storage temperature: 20 °C.
Protect from frost.

8. Exposure controls/personal protection

Ingredients with occupational exposure limits to be monitored:

CAS no.	EINECS no.	limit value
Hazardous substance name		

Personal protective equipment

not necessary

Wash hands before breaks and after work.

9. Physical and chemical properties

Appearance

Form : Liquid

Colour : beige

Odour : characteristic

Data relevant to safety

Boiling range 100-195 °C

Flash point: --- °C
Method :

Density at: 20°C 1,01-1,02 g/ml

Solubility in water:
at 20°C 90%
partial miscible

PH value: 10 g/l H₂O(20°) 7,0-8,0

Outflow time with 20°C 25-50 sec
Method : DIN EN ISO 2431

Further Information

10. Stability and reactivity

Hazardous reactions

No hazardous reactions known.

Hazardous decomposition products

No hazardous decomposition products known.

11. Toxicological information

No toxicological data are available.

12. Ecological information

Ecological data are not available
Do not discharge product unmonitored into the environment.

13. Advice on disposal

Disposal / product

In accordance with regulations for special waste, must be taken to an authorised special waste disposal site or incineration plant.

Code

20 01 13

Disposal / contaminated packaging
15 01 02

14. Transport information

Not classified as hazardous goods in accordance with GGVS/GGVE,
RID/ADR, ADNR, IMDG, IATA-DGR

15. Regulatory information

Labelling

The product does not require a hazard warning label in accordance
with EC directives/the relevant national laws.

Hazard symbols

R phrases

S phrases

S2

Keep out of the reach of children.

Water hazard class / source

(german only)

Other regulations, restrictions and prohibition regulations

16. Other information

List of R-Phrases/wording of the ingredients classified under
point 3

R53 May cause long-term adverse effects in the aquatic
environment

R65 Harmful: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

All data are based on our current knowledge and information.
They are intended to describe our products with regard to safety
requirements and thus do not purport to warrant any specific
qualities.