

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML
- · Article number: 04097
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- · Application of the substance / the mixture Spray varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTĬP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h 17:00h)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Solvent naphtha (petroleum), light arom.

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	10-12.5%

- GB

(Contd. of page 1)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

G1 G 10 C 0 G 0		ntd. of page
CAS: 106-97-8	butane	10-12.5
EINECS: 203-448-7	🚱 Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119474691-32-xxxx		
CAS: 75-28-5	isobutane	10-12.5
EINECS: 200-857-2	♦ Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119485395-27-xxxx		
EC number: 918-668-5	Solvent naphtha (petroleum), light arom.	1-2.5%
Reg.nr.: 01-2119455851-35-xxxx	♠ Flam. Liq. 3, H226	
	& Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	₹ STOT SE 3, H335-H336	
CAS: 1330-20-7	xylene	1-2.5%
EINECS: 215-535-7	♠ Flam. Liq. 3, H226	
Index number: 601-022-00-9	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
Reg.nr.: 01-2119488216-32-xxxx	*	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients	with limi	t values	that require	monitoring	at the	worknlace.

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

1330-20-7 xylene

WEL | Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

(Contd. of page 4)

- $\cdot \textit{Respiratory protection:} \ Not \ required.$
- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical an	nd chemical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	Different according to colouring
Odour: Odour threshold:	Solvent-like Not determined.
pH-value:	Not determined.
Change in condition	W 1, 1
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	<0 °C (<32 °F)
	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C (> 392 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
Density at 20 °C (68 °F):	0.735 g/cm³ (6.134 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	85.5 %
EU-VOC:	628.3 g/l

(Contd. on page 6)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

(Contd. of page 5)

· EU-VOC in %:	85.49 %	
· Solids content: · 9.2 Other information	20.3 % No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values relev	ant for classification:
67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50/4 h	39 mg/m3 (rat)
Hydrocarb	ons, C9-C1	2, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	13100 mg/m3 (rat)
106-97-8 b	utane	
Inhalative	LC50/4 h	658000 mg/m3 (rat)
Solvent na	phtha (petro	oleum), light arom.
Oral	LD50	3592 mg/kg (rat) (OECD401)
Dermal	LD50	>3160 mg/kg (rab) (OECD402)
Inhalative	LC50/4 h	>6193 mg/m3 (rat)
1330-20-7	xylene	
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4h	22.1 mg/m3 (rat)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>15000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Indeal ations	IC50/1h	>2.8 mg/m3 (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

(Contd. of page 6)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
67-64-1 acetone	
EC50 / 48 h	8800 mg/l (daphnia magna)
LC50 / 48 h	2262 mg/l (daphnia magna)
LC50 / 96 h (static)	5540 mg/l (fish)
Hydrocarbons, C9-	C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
EC50 / 48 h	10-22 mg/l (daphnia magna)
EC50 / 72 h	4.6-10 mg/l (algae)
LC50 / 96 h	10-30 mg/l (fish)
Solvent naphtha (pe	etroleum), light arom.
EC50 / 24 h	150 mg/l (daphnia magna)
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	3.77 mg/l (fish)
1330-20-7 xylene	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue				
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances			
15 01 04	metallic packaging			

(Contd. on page 8)

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

(Contd. of page 7)

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport informat	
14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F- D , S - U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity
	above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anna	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

	(Contd. of page 8
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
\cdot IMDG	
· Limited quantities (LQ)	IL
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017 Version number 62 Revision: 30.03.2017

Trade name: MOTIP® BRAKE CALIPER SPRAY YELLOW 400 ML

(Contd. of page 9)

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.