

Page 1 of 11
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 14.11.2011 / 0015
Replaces revision of / Version: 19.01.2011 / 0014
Valid from: 14.11.2011
PDF print date: 14.11.2011
WD-40

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

WD-40

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Corrosion protection
Lubricant
Rust remover

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

WD40 Company Limited UK, PO Box 440 , Kiln Farm, Milton Keynes, MK11 3LF
Telephone 01908 555400, Fax 01908 266900
info@wd40.co.uk

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

1.4 Emergency telephone

Advisory office in case of poisoning:

Telephone number of the company in case of emergencies:

Tel.: +49 (0) 700 / 24 112 112 (WDC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments).

Flammable, R10
Xn, Harmful, R65
R66
R67

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments).

Symbols: Xn

Indications of danger:

Harmful

R-phrases:

10 Flammable.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.



S-phrases:

2 Keep out of the reach of children.

23 Do not breathe vapour/spray.

24 Avoid contact with skin.

35 This material and its container must be disposed of in a safe way.

51 Use only in well-ventilated areas.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Voluntary:

16 Keep away from sources of ignition - No smoking.

3/9/14 Keep in a cool, well-ventilated place away from ... (incompatible materials to be indicated by the manufacturer).

Additions:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

Free from:

CFC

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Registration number (ECHA)	01-2119463258-33-XXXX
Index	---
EINECS, ELINCS	919-857-5
CAS	CAS n.v.
content %	60-80
Symbol	Xn
R-phrases	10-65-66-67
Classification categories / Indications of danger	Flammable, Harmful
Hazard class/Hazard category	Hazard statement
Flam. Liq./3	H226
Asp. Tox./1	H304
STOT SE/3	H336

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****Inhalation**

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Inhalation:

Headaches

Nausea

Dizziness

Irritation of the respiratory tract

Effects/damages the central nervous system

With long-term contact:

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Diarrhoea

Danger of aspiration

Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam

CO₂

Extinction powder

Cool container at risk with water.

Unsuitable extinguishing media

Water

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Explosive vapour/air mixture

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 14.11.2011 / 0015
 Replaces revision of / Version: 19.01.2011 / 0014
 Valid from: 14.11.2011
 PDF print date: 14.11.2011
 WD-40

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

- Ensure good ventilation.
- Keep away from sources of ignition - Do not smoke.
- Take measures against electrostatic charging, if appropriate.
- Avoid contact with eyes or skin.
- Do not carry cleaning cloths soaked in product in trouser pockets.
- Observe directions on label and instructions for use.
- Use working methods according to operating instructions.
- General hygiene measures for the handling of chemicals are applicable.
- Wash hands before breaks and at end of work.
- Keep away from food, drink and animal feedingstuffs.
- Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

- Keep out of access to unauthorised individuals.
- Not to be stored in gangways or stair wells.
- Store product closed and only in original packing.
- Do not store with flammable or self-igniting materials.
- Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").
- Store in a dry place.
- Store cool

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m3

Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		Content %:60-80
WEL-TWA: 800 mg/m3	WEL-STEL: ---	---	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)		
Chemical Name	Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---	
BMGV: ---	Other information: ---		
Chemical Name	Paraffin wax, fume		Content %:
WEL-TWA: 2 mg/m3	WEL-STEL: 6 mg/m3	---	
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Use-Area	Exposure-Route	Exposure-Pattern	Descriptor	Value	Unit	Note
Worker	Human - dermal	Long term, systemic effects	DNEL (Derived No Effect Level)	208	mg/kg bw/day	
Worker	Human - inhalation	Long term, systemic effects	DNEL (Derived No Effect Level)	871	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL (Derived No Effect Level)	125	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL (Derived No Effect Level)	125	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL (Derived No Effect Level)	185	mg/m3	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN 374)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

Amber

Odour:

Characteristic

Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	<-66 °C (ASTM D 97)
Initial boiling point and boiling range:	176 °C ((760 mmHg))
Flash point:	47 °C (Tag, open cup)
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-% (Naphtha (petroleum), hydrotreated heavy)
Upper explosive limit:	8,0 Vol-% (Naphtha (petroleum), hydrotreated heavy)
Vapour pressure:	Not determined
Vapour density (air = 1):	>1
Density:	0,817 g/ml (21°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<1 cSt
Explosive properties:	Possible build up of explosive/highly flammable vapour/air mixture., Product is not explosive.
Oxidising properties:	Not determined
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

WD-40

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.

Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other toxicity data:						Classification according to calculation procedure.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Respiratory or skin sensitisation:						Not sensitizing
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, reddening of the skin

Paraffin wax, fume						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						diarrhoea

SECTION 12: Ecological information

WD-40							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Toxicity to fish:	NOELR	28d	0,13	mg/l	(Oncorhynchus mykiss)	QSAR	
Toxicity to fish:	LC50	96h	>1000	mg/l	(Oncorhynchus mykiss)	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	48h	>1000	mg/l	(Daphnia magna)	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOELR	21d	0,23	mg/l	(Daphnia magna)	QSAR	
Toxicity to algae:	ErC50	72h	>1000	mg/l	(Pseudokirchneriella subcapitata)	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	NOELR	72h	100	mg/l	(Raphidocelis subcapitata)	OECD 201 (Alga, Growth Inhibition Test)	groth rate
Toxicity to algae:	NOELR	72h	3	mg/l	(Pseudokirchneriella subcapitata)	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	EbC50	72h	>1000	mg/l	(Pseudokirchneriella subcapitata)	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other adverse effects:							n.d.a.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

14 06 03 other solvents and solvent mixes

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

15 01 04 metallic packaging

15 01 01 paper and cardboard packaging

Dispose using dual system.

SECTION 14: Transport information

General statements

UN number:

3295

Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 3295 HYDROCARBONS, LIQUID, N.O.S.

Transport hazard class(es):

3

Packing group:

III

Classification code:

F1

LQ (ADR 2011):

5 L

LQ (ADR 2009):

7

Environmental hazards:

Not applicable

Tunnel restriction code:

D/E

**Transport by sea (IMDG-code)**

UN proper shipping name:

HYDROCARBONS, LIQUID, N.O.S.

Transport hazard class(es):

3

Packing group:

III

EmS:

F-E, S-D

Marine Pollutant:

n.a

Environmental hazards:

Not applicable

**Transport by air (IATA)**

UN proper shipping name:

Hydrocarbons, liquid, n.o.s.

Transport hazard class(es):

3

Packing group:

III

Environmental hazards:

Not applicable

**Special precautions for user**

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

For classification and labelling see Section 2.

Observe restrictions:

Yes

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Observe law on protection of expectant mothers (German regulation).

VOC (1999/13/EC):

~67,2% w/w

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

EUF0003

Revised sections:

2, 3, 8, 11, 12, 14, 16

The following statements are the indicated R-phrases / H-phrases and classification codes (GHS/CLP) for the ingredients (listed in Section 3).

10 Flammable.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Flam. Liq.-Flammable liquid

Asp. Tox.-Aspiration hazard

STOT SE-Specific target organ toxicity - single exposure - narcotic effects

Legend:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database

LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LMBG Lebensmittel- und Bedarfsgegenständegesetz (= Foodstuffs and Commodities Law)
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PC product category (= Chemical product category)
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
 WHO World Health Organization

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.